

5440A-7003 | 低热电势测试线（铲式接头） 选件



产品概述: 5440A-7003 | 低热电势测试线（铲式接头） 选件

The 5440A-7003 is a set of three test lead cables. These test leads use lower thermal emf material connectors than standard test leads, minimizing the emf caused by the temperature difference between the ends of the leads. There are two test leads that are 24 inches in length and one test lead that is 48 inches long. Each test lead is a shielded, two-conductor cable with a separate guard/shield connection.

Length: Two test leads that each are 24 in \pm 1 in (61 cm \pm 2.5 cm) long; one test lead that is 48 in \pm 1 in (122 cm \pm 2.5 cm) long

Connector style: Spade lug sized for 1/4 inch (6.35 mm) diameter terminals

Connector materials: Copper space lug with gold plating over silver plating (contains no nickel)

Cable type: Two conductor shielded cable (Belden 8719 or equivalent)

Signal conductors: 16 AWG tinned copper with 19 x 29 stranding

Thermal EMF: Less than 1.3 μ V per $^{\circ}$ C when measured while engaged in a five-way binding post of Tellurium Copper Alloy 145, half hard

Leakage resistance between two conductors or between either conductor and shield: Greater than $1.0 \times 10_{13}$ ohms per 100 ft at 45 $^{\circ}$ C and 75 % R.H.



型号

5440A-7003
低热电势测试线（铲式接头）选件



Fluke. 让您的工作畅通无阻。

福禄克测试仪器（上海）有限公司 电话：400-810-3435 ©2025 福禄克公司
07/2025
北京福禄克世禄仪器维修和服务有限公司 电
话：400-615-1563 未经许可，本文档禁止修改
福禄克测试仪器（上海）有限公司上海维修中心 电
话：021-54402301, 021-54401908分机269
福禄克测试仪器（上海）有限公司深圳第一特约维修点
电话：0755-86337229