

技术资料

## 2626-S | 备用传根器,标准精度



## 产品概述: 2626-S | 备用传根器,标准精度

One of the potential advantages of a digital thermo-hygrometer is that instead of sending the entire unit out for calibration, you can simply swap sensors and send only the sensors due for calibration out of the lab. The 1620A "DewK" Thermo-Hygrometer allows you to swap sensors without shutting it down or discontinuing your other readings.

Smart sensors make this possible because all of the calibration information is contained inside the sensor. Your costs are reduced because the 1620A never needs to be calibrated since it is only a display. Spare sensors like the 2626-S are less expensive to store, ship and recalibrate than an extra chart recorder.

The 2626-S is a spare standard-accuracy smart sensor for all models of the "DewK" Thermo-Hygrometer.

产品规格: 2626-S | 备用传根器,标准精度



## 型号



2626-S 备用传根器,标准精度



## Fluke. 让您的工作畅通无阻。

福禄克测试仪器(上海)有限公司 电话:400-810-3435 ©2025 福禄克公司

06/2025

北京福禄克世禄仪器维修和服务有限公司 电

话:400-615-1563 未经许可,本文档禁止修改

福禄克测试仪器(上海)有限公司上海维修中心 电话: 021-54402301, 021-54401908分机269

福禄克测试仪器(上海)有限公司深圳第一特约维修点

电话:0755-86337229