

技术资料

# Fluke 922 Airflow Meter/Kit



## 主要特性

Fluke 922 was designed and built for how (and where) you do your job, with performance, ruggedness and ease of use, setting the Fluke 922 apart from the competition. The bright white display and ruggedized holster and wrist strap let you take the Fluke 922 into less than ideal environments. The color-coded hoses help you keep track of where your readings are coming from. The simple, intuitive interface means you can measure pressure, velocity, or airflow at the push of a button. The Fluke 922 helps you analyze airflow. Easily.

- Powerful meter provides differential and static pressure, air velocity and flow readings
- Convenient colored hoses help proper interpretation of pressure readings
- Easy to use without sacrificing performance
- Bright, backlit display for clear viewing in all environments
- User-defined duct shape and size for maximum airflow accuracy
- Resolution down to 0.001 in H<sub>2</sub>O
- 99 point data storage capacity
- Min/Max/Average/Hold functions for easy data analysis
- Auto power off saves battery life



# 产品概述: Fluke 922 Airflow Meter/Kit

Analyze airflow. Easily. The 922 Micromanometer.

Today's HVAC technicians want a simple solution for diagnosing ventilation issues. Differential pressure measurements only tell part of the story. Technicians also want to measure air velocity and flow, without having to resort to expensive, difficult to use, specialist tools. The Fluke 922 makes airflow measurements easy by combining three tools: differential pressure, airflow, and velocity into a single, rugged meter.

Use the Fluke 922 micromanometer to:

- Measure pressure drops across key HVAC equipment to drive peak performance and extend equipment life
- Match ventilation to occupant loads
- Monitor indoor vs. outdoor pressure relationships and manage the building envelope
- Promote indoor comfort and quality
- Perform duct traversals for accurate airflow readings

产品规格: Fluke 922 Airflow Meter/Kit



# 型号



#### Fluke-922/KIT

- Fluke 922 空气流量检测仪
- 12 英寸皮托管
- 两个橡胶软管
- TPak 磁条
- TPak 带,9 英寸
- TPak 锁片
- 四节 1.5 V AA 碱性电池
- 用户手册
- 硬便携包



### Fluke. 让您的工作畅通无阻。

福禄克测试仪器(上海)有限公司 电话:400-810-3435 ©2025 福禄克公司

07/2025

北京福禄克世禄仪器维修和服务有限公司 电

话: 400-615-1563 未经许可,本文档禁止修改

福禄克测试仪器(上海)有限公司上海维修中心 电话: 021-54402301, 021-54401908分机269

福禄克测试仪器(上海)有限公司深圳第一特约维修点

电话:0755-86337229